

## Tapes – Glass

### GENERAL INFORMATION

OBA carries a large and varied range of glass tapes in plain woven, varnished, adhesive and non adhesive forms. These are designed for use in Class F(155°C) or higher temperatures environments.

Please contact your local OBA office to obtain the right tape for your application. Most glass tapes are supplied in 50 metre rolls (Variations will be advised by OBA)

### APPLICATIONS

Typical uses are:

- Electric Motor Windings
- Coils
- Transformers
- Chokes

### TYPICAL TYPES & SIZES

<b>Woven Glass</b>			
"B" Weave	Width	12, 20, 25, & 50mm	
	Thickness	0.90, 0.125, 0.175 & 0.225mm	
"R" Weave	Width	12, 20, 25, 31, 37, & 50mm	
	Thickness	0.90, 0.125, 0.175 & 0.225mm	
<b>Varnished Glass</b>	Various grades of Varnished Glass tape are available upon request		
<b>Raised (Welded) Edge Glass</b>	Width	50 & 75mm (3mm edge)	
	Edge thickness	3, 4, 5, 6 & 7mm	
<b>Adhesive Glass</b>			
A3130	Width	8, 12, 18, 24, 25, 36 & 48mm	
510	Width	12, 20, 25, & 50mm	
	Thickness	0.90, 0.125, 0.175 & 0.225mm	
590	Width	12, 20, 25, & 50mm	
	Thickness	0.90, 0.125, 0.175 & 0.225mm	
<b>Composite Glass Types</b>			
Glass / Polyester	Width	19 & 25mm	
	Thickness	0.09, 0.13 & 0.23mm	
Glass / Rubber	Width	6, 9, 12, 18, 20, 25, 32, 40, 50 & 1060mm	
Glass / Silicon	Width	12 & 18mm	